



Aluette swing gate

The Aluette swing gate is made completely of aluminium, making it highly resistant to corrosion and giving it a very long service life. It has a maximum passage width of 1.5 m and a maximum height of 2 m.

The Aluette swing gate is usually installed next to an Aluette sliding gate as a gateway for pedestrians. To create a visual unity between the swing gate and the sliding gate, the Aluette swing gate comes in 7 different versions:

- Standard with bars (square or round)
- Standard with Romance bars
- Combination of bars and lamellae
- Closed lamellae
- Lamellae with spacing 15 or 80 mm
- Perforated plate
- Cross



It is naturally also possible to use the Aluette swing gate as an independent gate for smaller entrances.

Just like the sliding version, the Aluette swing gate is available in different standard colours, but can also be delivered in a personalized RAL colour.



www.kopal.be



info@kopal.be

Aluette swing gate



Posts, frame & locking system

The posts for the Aluette swing gate are square tubular profiles made of aluminium measuring 100/100/5 mm, with an aluminum cover. The frame of the Aluette swing gate is made of aluminium tubular profiles measuring 26/26/1.6 mm. The frame is fixed on the post using hinges in stainless steel, which allow the gate to open at 180°. The Aluette swing gate has an incorporated cylinder lock made of stainless steel with hook lock, including 3 keys.

Finish

Pretreatment: degreasing, chemical scouring and chromatising. Then coated with a polyester powder coating in a standard Kopal colour. Other colours are available on demand. All accessories ar made of inox or aluminium.

Fillings

- ① Standard square bars of 26/26/1.6 mm at a distance of 15 cm a.o.a.
- ② Romance bars: the Romance bars offer a very high rigidity and give the Aluette swing gate a beautiful, decorative look. To be advised for gates higher than 1.80 m.
- ③ Lamellae: With concatenating lamellae, the Aluette swing gate offers an optimal privacy. The lamellae have a tongue and groove system, which makes them fit perfectly. Dimensions of the lamellae: 80 x 25 mm.

Standard height Aluette swing gate (m)	Standard width Aluette swing gate (m)
1.00	1.00
1.20	1.20
1.50	1.50
1.80	
2.00	

Standard height Aluette swing gate (m)	Standard width Aluette swing gate (m)
1.00	1.00
1.20	1.20
1.50	1.50
1.80	
2.00	

- ④ Combined filling: lamellae and bars. Aluette swing gate with a combination of 1/3 concatenated lamellae and 2/3 bars. The lamellae are placed at the bottom and the bars on top, giving the gate a stylish and modern look. For the bars, one can choose between standard square bars or Romance bars.
- ⑤ Perforated plate. By using perforated aluminium plates, one can obtain a modern touch in the fence, whilst providing a visual protection. One can choose between two versions: round perforations or square perforations (R10 T15 or C8 U24).
- ⑥ Distance: The gate is filled with lamellae of 80 x 20 mm, that are placed at a distance of 15 mm of each other, thus creating a half open protection. This guarantees the privacy.
- ⑦ Cross: The gate is filled with concatenating lamellae and crosses on top. This creates an elegant swing gate with a reference to a filling type that is often used for wooden gates.

STANDARD COLOURS	RAL CODE
moss green	RAL 6005
pine green	RAL 6009
stone gray	RAL 7030
quartz gray	RAL 7039
anthracite gray	RAL 7016
pure white	RAL 9010
brilliant black	RAL 9005bl
mat black	RAL 9004m
Other colours on demand	
Shown colours can differ from the true colours. Always use colour samples to choose your colour.	

Kopal NV/SA
Ieperstraat 75A
8610 Kortemark

Product sheet Aluette swing gate EN 02-2018

+32 (0) 51 57 09 00
+32 (0) 51 57 09 88
info@kopal.be

Your Distributor: